



## 2016 Weight Rule

Weight will be taken after the race. Weights may be adjusted at the Promoter's discretion.

### Power Stock **weights are with driver in seat**

Configuration	Minimum Weight	Front 57% of Min.	Min right side weight
350 engine oem 4V	3400	1938	1598
305 engine oem 4V	3000	1710	1410
602 Crate Engine	3300	1881	1551

### Thundercar

Configuration	Minimum Weight	Front 53% of Min.	Left 56 Max %
Holley 500 cfm 2V	3100	1643	1736
602 Crate Engine	3000	1590	1680

### Big 8

Engine	Minimum Weight	Front 49% of Min.	Left 58 Max %
<b>GM 604 Crate</b> 650 cfm & 6700 chip	2800	1372	1624
<b>Big 8</b>			
<b>Big 8 Wegner LS</b> 40# must be attached to the engine block	2825	1384	1639
Solid axles and Spool	Deduct 20#	Deducts must be declared before start of event.	
Single piston calipers	Deduct 30#		
2 piston calipers	Deduct 15#		

### Super Latemodel

Engine	Carburetor	Minimum Weight	Left 58.2 Max %
Tour Motor	500 cfm 2 bbl.	2750	1601
Hamner 7600 rpm	500 cfm 2 bbl.	2700	1571
Wegner Spec	500 cfm 2 bbl.		
MEP 7600 rpm	500 cfm 2 bbl.		
ACE	500 cfm 2 bbl.		
Elko Concept	500 cfm 2 bbl.	2650	1542
604 GM Crate Motor	650 cfm 4 bbl.		
No Other Motor Combinations Allowed			
All Rev limiter settings to be verified with tech officials before event			

## Big 8 Weight Matrix

<b>GM 604 Crate</b> 650 cfm & 6700 chip & <b>Big 8</b> with updates			
	Total	Front	Left Max%
Without solid axles and spool & with 4 piston calipers	2800	1372	1624
Without solid axles and spool & with single piston caliper	2770	1357	1607
Without solid axles and spool & with dual piston caliper	2785	1365	1615
With solid axles and spool & 4 piston calipers	2780	1362	1612
With solid axles and spool & single piston caliper	2750	1348	1595
With solid axles and spool & dual piston caliper	2765	1355	1604

<b>Big 8 Wegner LS</b> 40# must be attached to the engine block			
	Total	Front	Left Max%
Without solid axles and spool & with 4 piston calipers	2825	1384	1639
Without solid axles and spool & with single piston caliper	2795	1370	1621
Without solid axles and spool & with dual piston caliper	2810	1377	1630
With solid axles and spool & 4 piston calipers	2805	1374	1627
With solid axles and spool & single piston caliper	2775	1360	1610
With solid axles and spool & dual piston caliper	2790	1367	1618