

# ELKO!

**Racing • Eve of Destruction • Drive-In**

## 2019 Weight Rule

Weight will be taken after race. Weights may be adjusted at the Promoter's discretion.

### Power Stock

Configuration	Minimum Weight	Front	Left
350 engine oem 4V	3400	57% MIN	55% MAX
602 Crate Engine	3400	57% MIN	55% MAX
305 engine oem 4V	3000	57% MIN	55% MAX

### Thunder Car

Any Combinations of upgrades allowed

#### Holley 500cfm 2B

Configuration	Minimum Weight	Front	Left
Base Weight	3100	52% MIN	58% MAX

#### 602 Crate

Configuration	Minimum Weight	Front	Left
Base Weight	3050	52% MIN	58% MAX

### Big 8 Late Models

1lb Per Lap Fuel Allowance Allowed

#### 604 Crate Stock

Configuration	Minimum Weight	Front	Left
Base Weight	2775	49% MIN	58% MAX
with Koni Shocks	2800	49% MIN	58% MAX
with Torque Sensing Diff	2850	49% MIN	58% MAX
with Koni's & Torque Sensing Diff	2875	49% MIN	58% MAX

#### Updated 604 Crate or Limited Concept Engine

Configuration	Minimum Weight	Front	Left
Base Weight	2825	49% MIN	58% MAX
with Koni Shocks	2850	49% MIN	58% MAX
with Torque Sensing Diff	2900	49% MIN	58% MAX
with Koni's & Torque Sensing Diff	2925	49% MIN	58% MAX

#### Chrysler over 362

Configuration	Minimum Weight	Front	Left
Base Weight	2870	49% MIN	58% MAX
with Koni Shocks	2895	49% MIN	58% MAX
with Torque Sensing Diff	2945	49% MIN	58% MAX
with Koni's & Torque Sensing Diff	2970	49% MIN	58% MAX

#### LS Engine

(40# mounted directly to engine block)

Configuration	Minimum Weight	Front	Left
Base Weight	2900	49% MIN	58% MAX
with Koni Shocks	2925	49% MIN	58% MAX
with Torque Sensing Diff	2975	49% MIN	58% MAX
with Koni's & Torque Sensing Diff	3000	49% MIN	58% MAX